TECHNICAL DATASHEET

Exterior electrical spraying machine COMPACT-PRO 70 - 400V | ref.30960





Motor electrical 15 kW Motor power 400 V - 32 A - 50 & 60 Hz Supply Rotation speed 2500 tr/min 28 L Hydraulic system Compressor twin-cylinder Compressor flow-rate at 4 bar 400 L/min Hydraulic controls manual Mixer rotation speed setting yes Pump speed setting yes Automatic accelerator control ves Mixer tank capacity 230 L Mixer drainage plug 3 inches Water sprinkler pipe ves Water meter yes Mixing paddle yes Rotation 2 directions Loading height 86 cm Hopper capacity 200 L Hopper drainage plug 3 inches from 0 to 70 L/min Variable flow-rate Pressure from 0 to 40 bar up to 6 mm Max. grain size **MAP 11** Pump Pump reverse operation ves 140 bar HP washer max pressure HP washer flow-rate 11 L/min Overall length with tow bar 3,55 m Overall length without tow bar 3,09 m 1,26 m Height at the highest point 1,29 m Weight when full with oil 710 kg Noise level 94 Lwa Delivery height 50 m Max. hose length 60 m

Easy-to use electrical versatile spraying machine for outdoor spraying.

Made in France, it is equipped with a button control panel for simplified use, an automatic accelerator and a water dosing meter.

APPLICATIONS

Large wall jobs in hydraulic coatings, mortars, E.W.I. ...

Delivered with

- a MAP 11 pump
- a Ø35 x 13,30 m product hose M50 x F35
- a Ø35 x 13,30 m product hose M35 x F35
- a Ø25 x 5 m hose M35 x M25
- a Ø10 x 33 m air hose
- a spraying lance
- eight nozzles (Ø8, 10, 12, 14, 16, 18, 20 & 22)
- three grouting nozzles (Ø10, 12 & 14)
- two Ø30 cleaning balls
- two Ø50 cleaning balls
- a greasing pump with a grease cartridge
- a pressure controller adapter
- a pressure controller
- a complete high pressure washer lance
- a 10 m high pressure washer hose
- a storage carry-case
- a suspension strap

