TECHNICAL DATASHEET

Exterior diesel spraying machine COMPACT-PRO 80 | ref.30967



Kohler KDW 1404 Motor Motor power 24,5 kW Diesel Fuel 251 Diesel tank liquid Cooling 2500 tr/min Rotation speed Number of cylinders 4 Consumption 4,1 L/h Hydraulic system 28 L Compressor twin-cylinder Compressor flow-rate at 4 bar 400 L/min Engine monitoring panel complete Hydraulic controls manual Mixer rotation speed setting ves Pump speed setting yes Automatic accelerator control yes Mixer tank capacity 230 L Mixer drainage plug 3 inches Water sprinkler pipe yes Water meter yes Mixing paddle yes Rotation 2 directions 86 cm Loading height 200 L Hopper capacity Hopper drainage plug 3 inches from 0 to 80 L/min Variable flow-rate Pressure from 0 to 40 bar Max. grain size up to 6 mm **MAP 11** Pump reverse operation HP washer max pressure 140 bar HP washer flow-rate 11 L/min Overall length with tow bar 3,55 m Overall length without tow bar 3,09 m 1,26 m Overall width Height at the highest point 1,29 m Weight when full with oil and diesel 735 kg Noise level 101 Lwa Delivery height 50 m Max. hose length 60 m

Easy-to use diesel versatile spraying machine for outdoor spraying.

Made in France, it is equipped with a button control panel for simplified use, an automatic accelerator and a water dosing meter.

APPLICATIONS

Large wall jobs in hydraulic coatings, mortars, E.W.I. ...

Delivered with

- a MAP 11 pump
- a Ø35 x 13,30 m product hose M50 x F35
- a Ø35 x 13,30 m product hose M35 x F35
- a Ø25 x 5 m hose M35 x M25
- a Ø10 x 33 m air hose
- a spraying lance
- eight nozzles (Ø8, 10, 12, 14, 16, 18, 20 & 22)
- three grouting nozzles (Ø10, 12 & 14)
- two Ø30 cleaning balls
- two Ø50 cleaning balls
- a greasing pump with a grease cartridge
- a pressure controller adapter
- a pressure controller
- a complete high pressure washer lance
- a 10 m high pressure washer hose
- a storage carry-case
- a suspension strap

