

OPTIMIX 30

Spraying machines for slurry products | reference : 3B03301000



Sprayer for slurry, fibrous and decorative surface coatings, etc. Especially used for adhesive mortars and acrylic renders.

Optimix 30 is a small versatile sprayer.

TECHNICAL DATA

Hopper capacity	59 L
Power supply	230 V- 16 A / 50 Hz
Motor power	1.5 kW
Spraying pressure	0 to 20 bar
Spraying flow rate	0 to 10 L/min
Integrated compressor	yes
Compressor flow rate	366 L/min
Max. grain size	2 mm
Max. spraying distance	20 meters*
Dimensions (l x w x h)	108 x 64 x 73 cm
Noise level	96 Lwa
Weight	98 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- One Ø25 mm x 10 LM air/product hose
- 1 EWI spray lance case containing:
 - 1 ABS spray lance for EWI
 - Air pressure adjustment
 - 5 spraying nozzles (Ø6, 7, 8, 10, 12 mm)
 - 3 pointing nozzles (Ø10, 12 and 14 mm)
 - 2 cleaning balls
 - 1 cleaning auger
 - One Ø7 Allen key

MIXER®