

OPTIMIX 40

MORTAR VERSION

Spraying machines for slurry products | reference : 3B03312000



Sprayer for slurry, fibrous and decorative surface coatings, fire proofing and repair mortars clay.

Optimix 40 is a versatile sprayer.

TECHNICAL DATA

Hopper capacity	100 L
Power supply	230 V- 16 A / 50 Hz
Motor power	2.2 kW
Spraying pressure	0 to 20 bar*
Integrated compressor	yes
Compressor flow rate	366L/min
Compressor motor power	2.2 kW / 3CV
Max. compressor pressure	10 bar
Spraying flow rate	0 to 20 L/min
Integrated vibrator	yes
Max. grain size	3 mm
Dimensions (l x w x h)	130 x 70 x 75 cm
Noise level	96 Lwa
Weight	143 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and lenght of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- One Ø32 mm x 10 LM air/product hose
- 1 mortar spray lance case with:
 - 1 Alluminium spray lance for mortar
 - 8 spraying nozzles (Ø8, 10, 12, 14, 16, 18, 20, 22 mm)
 - 3 pointing nozzles (Ø10, 12, 14 mm)
 - 2 cleaning balls
 - 1 cleaning auger
 - One Ø7 Allen key
- 1 pressure controller with adapter

MIXER®