

PFT MULTIMIX 100


The affordable all-round mixer for modern building materials

The batch mixer can be used for a wide variety of materials such, as mortar, adhesive, plaster, grouting materials, putty and much more. The mixer scores with excellent mixing results, rapid bottom discharge, compact and robust design, and large transport rollers for the rigours of the construction site. Ideal for painters and stucco plasterers, screed installers and tilers, bricklayers and plasterers.

TECHNICAL DATA

Part no.	00 62 74 05
Drive motor	230 V, 1 Ph, 50 Hz, 2.0 kW, 42 rpm
Hopper content	100 litres
Mixing hopper	Steel
Operation	Start/Stop
Grain size	max. 32 mm Filling grille: LW 45x45
Filling height	1,190 mm
Output height	640 mm
Dimensions: L / W / H	720 / 690 / 1,190 mm
Weight	~80 kg

Kindly note:
All specifications are dependent on the products used.



ADVANTAGES AT A GLANCE



- 1** Excellent mixing result
From the offset arrangement of the mixing arms with mixing blades and wall scraper.
- 2** Quick cleaning
The mixing arms can be easily removed without tools and replaced individually.
- 3** Easy and dosed filling
This is possible through the sack opener on the protective grille.
- 3** Highest level of safety
Through the lockable protection grille.
- 4** Central operating switch
Provided with a quick stop button and a safety switch off for the drum cover.
- 5** Solid and sturdy design
Not too wide for any door and with its large transport wheels, it easily reaches up to the top.
- 6** Simple transport
Can be loaded easily by one person and fits in any estate car.
- 7** Easy and fast emptying
Whether in buckets, mortar buckets or wheelbarrows through a segment slider integrated in the bottom of the drum.

FIELDS OF APPLICATION

For the most materials:

- Cement mortar
- Plaster
- High-grade plaster
- Adhesive
- Plaster stone
- Terrazzo
- Putty
- Lime
- Screed
- Grouting
- Coating compounds
- Plaster and masonry mortar

ACCESSORIES | VARIANTS

PART NO.

- Extension cable 3 x 2.5 mm², BLU 2-16 A - 25 m 20 42 34 00
- MULTIMIX 140, 230 V, 1 Ph, 50 Hz 00 62 74 06
- MULTIMIX 140 drive over, 400 V, 3 Ph, 50 Hz 00 25 16 36

"drive over" means that the mixer easily fits over a conveying pump such as the ZP 3 or SWING.

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpften

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft-iphofen.de www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT MULTIMIX 100 - GB/06.18/PFT