

PFT MULTIMIX 140

The practical and powerful mixer


With its unique versatility, the robust mixer is designed for tough construction site use. The rear folding step and the sack opener allow simple and dosed filling of the large 140 litre drum. With a time saving of up to 60%, the mixer guarantees an efficient economic solution.



TECHNICAL DATA

Part no.	00 62 74 06
Drive motor	230 V, 1 Ph, 50 Hz, 2.3 kW, 29 rpm
Hopper content	140 litres
Mixing hopper	Steel
Operation	Start/Stop
Grain size	max. 32 mm Filling grille: LW 45x45
Filling height	1,210 mm
Output height	640 mm Height console: 290 mm
Dimensions: L / W / H	820 / 770 / 1,210 mm
Weight	~ 119 kg

Kindly note:
All specifications are dependent on the products used.



ADVANTAGES AT A GLANCE



- 1** Excellent mixing result
From the offset arrangement of the mixing arms with mixing blades and wall scraper.
- 1** Quick cleaning
The mixing arms can be easily removed without tools and replaced individually.
- 2** Simple and dosed filling
This is possible through the sack opener on the protective grille and the rear folding step.
- 2** Highest level of safety
Through the lockable protection grille.
- 3** Central operating switch
Provided with a quick stop button and a safety switch off for the drum cover.
- 4** Easy and fast emptying
Whether in buckets, mortar buckets or wheelbarrows through a segment slider integrated in the bottom of the drum.
100 litres suitable for wheelbarrows.
- Solid and sturdy design
Not too wide for any door and with its large transport wheels, it easily reaches up to the top.
- Easy transport
Can be easily loaded by one person.

FIELDS OF APPLICATION

For the most materials:

- Cement mortar
- Plaster
- High-grade plaster
- Adhesive
- Plaster stone
- Terrazzo
- Putty
- Lime
- Screed
- Grouting
- Coating compounds
- Plaster and masonry mortar

ACCESSORIES | VARIANTS

- | | |
|--|-------------|
| ■ Extension cable 3 x 2.5 mm ² ,
BLU 2-16 A - 25 m | 20 42 34 00 |
| ■ MULTIMIX 100, 230 V, 1 Ph, 50 Hz | 00 62 74 05 |
| ■ MULTIMIX 140 drive over, 400 V, 3 Ph, 50 Hz | 00 25 16 36 |

"drive over" means that the mixer easily fits over a conveying pump such as the ZP 3 or SWING.

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft-iphofen.de www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT MULTIMIX 140 - GB/06.18/PFT