

SINGLE-PHASE

Stator Ø	Ø 40	Ø 51	Ø 51	Ø 51	Ø 51	Ø 51	Ø 51	Ø 51	Ø 60	Ø 70	Ø 70	Ø 80	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 101
Description	MAP1	PC 830	MAP2	MAP3	JET1	JET2	8 - DX	8 - SX	MAP4	JET3	JET5	CAOUT 19	W 10 / 2,5	13	26	30	32	MAP5	MAP6	MAP7	W 20 / 1,5	1L6
STATOR TECHNICAL DATA																						
Length (mm)	170	135	210	210	310	310	135, 210 and 408	100, 160 and 210	265	405	405	259	270	270	270	270	270	270	270	270	270	270
Booster																						
Evo														yes	yes	yes						
Adjustable stator														yes					yes		yes	
With slits				yes																		yes
With anti-rotation														yes	yes	yes						
Max pressure (bar)	20	40	30	10 to 30	80 (60 SH) - 100 (70 SH)	140	15(60 SH/L135) - 30 (80 SH/L210) - 150 (80 SH/L405)	15 to 30	40	140 (70 SH) - 160 (80 SH)	140		25	30	25	20	25	30	10 to 30	40	10 to 30	10 to 30
Grain size (mm)	2	3	2	2	2	2	2	2	2	3	3	2	3	3	3	3	3	3	3	3	3	6
Flow-rate (L/min) at 400 rpm	5	12	10	10	10	10	10	10	9	13	13	19	20	13	20	25	30	35	35	27	35	60
Rubber hardness	70 SH	70 SH	70 SH	60 SH	60 SH and 70 SH	80 SH	60 SH - 80 SH	60 SH (L100) - 70 SH (L160 and 210)	70 SH	70 SH and 80 SH	70 SH	70 SH	70 SH	70 SH	70 SH	70 SH	60 SH	70 SH	60 SH	70 SH	60 SH	60 SH
Direction of rotation																						
Type of Mixer machine				Optimix 30	Flatspray 10	Flatspray 20, Flatmix 100				Flatspray 30						Light, Sprinter, Plus Mono	Light, Sprinter, Plus Mono	Light, Sprinter, Plus Mono	Light, Sprinter, Plus Mono			
APPLICATION																						
Gypsum based pre-mixed products					•	•			•	•	•		•	•	•	•	•	•	•	•	•	•
Gypsum / lime based pre-mixed products					•	•			•	•	•		•	•	•	•	•	•	•	•	•	•
Lime / cement based pre-mixed products					•	•			•	•	•		•	•	•	•	•	•	•	•	•	•
Self levelling floor screed																	•					•
Fireproofing mortars													•			•	•					
Traditional mortars																			•	•	•	•
Film fillers plasters	•	•	•	•	•	•	•	•	•	•	•	•		•				•				
Adhesive and acrylic mortars	•	•	•	•	•	•	•	•	•	•	•							•				
Paint	•	•	•	•			•	•														

INFORMATION GIVEN AS AN INDICATION.
WE RECOMMEND YOU TO CONTACT YOUR AREA MANAGER
AND TO CONSULT THE TABLES IN THE CATALOG TO CONFIRM YOUR CHOICE.

For more information and to stay updated on our news:
www.mixersrl.com



THREE-PHASE

Stator Ø	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 90	Ø 101	Ø 101	Ø 101	Ø 101	Ø 101	Ø 101	Ø 101	Ø 101
Description	1	2	3	4	5	6	W10/3	MICRO	POINT	POLO	JET4	MAP8	MP3L	MP8L	MP12L	JUMBO	2L6 - MAP10	JUMBO - MAP11	VG 55 - 11
STATOR TECHNICAL DATA																			
Length (mm)	270	270	270	270	270	270	270	270	270	270	450	265	375	379	535	535	535	535	535
Booster	yes	yes	yes			yes					yes								
Evo																			
Adjustable stator																yes	yes	yes	
With slits										yes							yes	yes	
With anti-rotation	yes	yes	yes	yes	yes	yes	yes	yes			yes		yes	yes	yes		yes	yes	yes
Max pressure (bar)	30	30	30	25	25	30	30	30	30	20	160 (Booster) - 140 (Straight)	30	30	30	30	10 to 30	10 to 20	10 to 30	150
Grain size (mm)	3	3	3	3	3	3	3	2	3	3	3	4	4	7	7	6	6	6	3
Flow-rate (L/min) at 400 rpm	22	27	32	40	50	22	22	7	22	35	21	55	22	40	60	60	60	110	24
Rubber hardness	70 SH	70 SH	70 SH	70 SH	70 SH	70 SH	60 SH	60 SH	70 SH	70 SH	80 SH	70 SH	70 SH	70 SH	70 SH	60 SH	60 SH	60 SH	70 SH
Direction of rotation																			
Type of Mixer machine	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard	Plus Top and Standard							Optimix 20 (5,5Kw)	
APPLICATION																			
Gypsum based pre-mixed products	•	•	•			•	•	•	•	•	•	•	•	•		•	•	•	•
Gypsum / lime based pre-mixed products	•	•	•			•	•	•	•	•	•	•	•	•		•	•	•	•
Lime / cement based pre-mixed products	•	•	•			•	•	•	•	•	•	•	•	•		•	•	•	•
Self levelling floor screed			•	•	•											•	•	•	
Fireproofing mortars			•	•						•									
Traditional mortars										•		•	•	•	•	•	•	•	
Film fillers plasters											•								•
Adhesive and acrylic mortars											•								•
Paint																			

INFORMATION GIVEN AS AN INDICATION.
WE RECOMMEND YOU TO CONTACT YOUR AREA MANAGER
AND TO CONSULT THE TABLES IN THE CATALOG TO CONFIRM YOUR CHOICE.

For more information and to stay updated on our news:
www.mixersrl.com

MIXER[®]

THREE-PHASE

Stator Ø	Ø 101 AND 114	Ø 101 AND 114	Ø 101 AND 123	Ø 123	Ø 123	Ø 123	Ø 123	Ø 145	Ø 145	Ø 145	Ø 145	Ø 159	Ø 166	Ø 190	Ø 190
Description	VIPER - DX	VIPER - SX	BORA	MIRAGE	MIRAGE / 75	2L74	MAP9	ESTRICH	MAGNUM	BIG FOOT	OSCAR	75 - 15	MP40	1,5L8	2L8

STATOR TECHNICAL DATA

Length (mm)	265 and 535	265 and 535	265 or 535	270 or 535	270 or 535	666	500	497	497	497	497	550	455	650	650
Booster															
Evo															
Adjustable stator			yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		yes	si
With slits															
With anti-rotation	yes	yes	yes (Ø101 L535)			yes		yes	yes	yes	yes	yes	yes		
Max pressure (bar)	20	20	10 to 30	10 to 30	10 to 30	10 to 25	10 to 30	10 to 25	10 to 30	10 to 30	10 to 30	35	30	10 to 30	10 to 30
Grain size (mm)	6	6	5	6	6	8	8	8	8	9	8	8	8	10	10
Flow-rate (L/min) at 400 rpm	55	55	60	140	80	320	320	200	300	240	240	300	250	470	450
Rubber hardness	60 SH and 70 SH	70 SH	70 SH	70 SH	70 SH	60 SH	60 SH	70 SH	60 SH	70 SH	70 SH	60 SH	60 SH	60 SH	60 SH
Direction of rotation						↻	↻					↻	↻	↻	↻
Type of Mixer machine	Remix (Ø101 L265 70SH)	Optimix 20													

APPLICATION

Gypsum based pre-mixed products	•	•	•			•	•	•	•	•	•	•	•		
Gypsum / lime based pre-mixed products	•	•	•			•	•	•	•	•	•	•	•		
Lime / cement based pre-mixed products	•	•	•			•	•	•	•	•	•	•	•		
Self levelling floor screed			•	•	•	•	•	•	•	•	•	•	•	•	•
Fireproofing mortars			•	•	•										
Traditional mortars	•	•		•	•	•	•	•	•	•	•	•	•	•	•
Film fillers plasters															
Adhesive and acrylic mortars															
Paint															

INFORMATION GIVEN AS AN INDICATION.
WE RECOMMEND YOU TO CONTACT YOUR AREA MANAGER
AND TO CONSULT THE TABLES IN THE CATALOG TO CONFIRM YOUR CHOICE.

For more information and to stay updated on our news:
www.mixersrl.com

